



INFA-MINI-JET AJM

Variable round filter series as cartridge filter

Highlights

Standard design features

Options

Highlights

The INFA-MINI-JET family is a versatile circular filter program. Customer-specific designs are available due to individual constructions. Because of an optional hot gas design, pressure resistance and gas-tightness, the fully automated cartridge filters ensure the separation of dust and powder products as well from exhaust air as from process gases.

During the filtration phase the cleaning of the filter cartridges is done in periodic intervals by pulses of compressed air (jet-pulse cleaning). The cartridge filter sizes cover a volume flow of 20 m³/h to 12,000 m³/h.

Standard design features

- > Basic module consisting of
 - > closed filter head
 - > filter elements and
 - > pneumatic cleaning unit
- > Expandable modular system for flexible adaptation to specific applications
- > Housing strength up to +/- 50 mbar g
- > Up to 80 °C
- > System can be equipped either with filter cartridges or filter bags
- > Easy filter media change from the clean gas side with quick clamp fastening
- > Design as
 - > top filter
 - > insert filter
 - > standing filter (dedusting filter)

Options

- > Modular supplements and accessories, e. g.
 - > filter housing
 - > hopper and dust bin
 - > level indicator within the dust bin
 - > butterfly valve
 - > rotary valve
 - > fan
 - > inspection cover
 - > secondary filter stage
- > All housing parts, internal parts or components in contact with the product / dust made of stainless steel
- > Housing strength up to +/- 0.5 bar g for pressure- or vacuum-pneumatic operation
- > Explosion protected design according to directive 2014/34/EU (ATEX)
- > Pressure-shock resistant design for reduced explosion pressure (e. g. 0.4 bar_g or 2.0 bar_g) with pressure relief or for maximum explosion pressure (9 bar_g)
- > Pressure resistant design up to 26 bar_g
- > Electronic control unit for filter cleaning controlled by timing cycle or differential pressure. Also for additional components (fan, rotary valve, etc.)
- > Control system and motors for special voltages, e. g. 500 V
- > Design for hot gases up to 240 °C
- > Filter media available in different qualities, e.g. FDA-conform for food industry
- > Sound absorbing kits for use in noise-sensitive environments
- > Exchange of filters elements on the raw gas side if not enough space in height is available
- > Electric heating of the filter housing including thermal insulation
- > Gastight design
- > Slewing mechanism for inspection cover on the clean gas side

Downloads

Dimension sheets Infa-Mini-Jet AJM
Information brochure

Typical application

Your contact person

You find the market place for used filter units [here](#).

You find all manuals PDF files [here](#).

You find all upcoming fair dates [here](#).

Sign up here for our [newsletter](#) and make sure to receive free tickets for our trade fairs.