



## Industry

### Application example

---

Dust-raising processes in metal machining are diverse. Wherever metals are ground, polished, milled or brushed, emissions in the form of dusts, fume, soot, vapours and gases occur. Here, it is necessary to take precautions.

Infastaub has been providing dedusting systems for metalworking companies for decades. Our products range from small filters for single applications to large-scale systems for central dedusting.

Waste foundry sand is conveyed from a silo via a screw conveyor to the **INFA-POWTRON loading system** and from there filled into a closed silo truck. The INFA-POWTRON loading system enables this process to be dustfree by sucking the dust containing air out of the truck through the double-walled loading bellow. The dust is then separated at the filter elements of the BKF. The filter elements are continuously cleaned from the accumulated dust in order to keep an optimum suction performance of the fan.

### Technical data

Filter type		Loading system BKF 10 P-S
Fan speed	[m³/h]	825
Filter area	[m²]	10
Filtermaterial		Polyester fleece
Filling level indicator		Rotary wing
Slack rope switch		2 pieces, automatic lowering of the cone during loading
Loading capacity	[tons/h]	max. 400



## Your contact person

---

You find the market place for used filter units [here](#).

You find all manuals PDF files [here](#).

You find all upcoming fair dates [here](#).

Sign up [here](#) for our [newsletter](#) and make sure to receive free tickets for our trade fairs.